



Cold Chamber

Technical Specification


Temperature Range: 2° C to 8 °C

Accuracy: ±1.5 °C

Uniformity: ±2.0 °C

Features

21 CFR PART-11 Compliance
Log data, Event data, Audit Trail data, E-Records & E-signatures, Graphical analysis & Data acquisition.



Sizes:

| Models | MK*-20CO | MK*-40CO | MK*-60CO | MK*-80CO | MK* -100CO | MK** -S100CO | MK** -S200CO | MK** -S300CO |
|----------|----------|----------|----------|----------|------------|--------------|--------------|--------------|
| Features | 200 Ltrs | 400 Ltrs | 600 Ltrs | 800 Ltrs | 1000 Ltrs | 1000 Ltrs | 2000 Ltrs | 3000 Ltrs |

Interior Dimension

| | | | | | | | | |
|--------------|-----|-----|------|------|------|------|------|------|
| Width in mm | 600 | 700 | 700 | 700 | 800 | 800 | 1600 | 1900 |
| Depth in mm | 400 | 600 | 800 | 800 | 800 | 800 | 750 | 800 |
| Height in mm | 850 | 950 | 1100 | 1450 | 1600 | 1600 | 1700 | 2000 |

Exterior Dimension

| | | | | | | | | |
|--------------|------|------|------|------|------|------|------|------|
| Width in mm | 760 | 860 | 860 | 860 | 960 | 960 | 1940 | 2240 |
| Depth in mm | 865 | 1060 | 1265 | 1265 | 1265 | 1265 | 1110 | 1160 |
| Height in mm | 1450 | 1550 | 1700 | 2050 | 2200 | 2200 | 1890 | 2190 |

Trays

| | | | | | | | | |
|--------------|---------------------|---|---|---|---|---|---|----|
| No of Trays | 2 | 3 | 3 | 4 | 4 | 4 | 8 | 12 |
| Type | Wiremesh Type | | | | | | | |
| Tray Spacing | Every ½" Adjustable | | | | | | — | — |

Power Supply

| | | | | | | | | |
|--------------|-------------------------|-------|-------|-----|-----|-----|-------|-------|
| Power Supply | Single Phase, 230V 50Hz | | | | | | | |
| Power Rating | 1KW | 1.5KW | 1.5KW | 2KW | 2KW | 2KW | 2.5KW | 2.5KW |
| Warranty | 12 Months | | | | | | | |

Other sizes also available as on requirement.

| Models | Material of Construction | |
|--------|--------------------------|---------------------|
| | Interior | Exterior |
| MK1 | S.S.304 Dull Finish | G.I. Powder Coated |
| MK2 | S.S.304 Dull Finish | S.S.304 Dull Finish |
| MK3 | S.S.316 Dull Finish | S.S.304 Dull Finish |

NOTE:

MK* :- MK1 / MK2 / MK3

MK**-S :- Split type Condensing Unit

MK**- S200CO & MK**- S300CO are Panel & Trolley type (Split Type Condensing Unit)

Optional Features

SCANNER
GSM TECHNOLOGY
HOOTER SYSTEM
EXTRA TRAY

