



## Deep Freezer

### Technical Specification

**Temperature Range:** UPTO - 40 °C

**Accuracy:**  $\pm 3$  °C

**Uniformity:**  $\pm 3$  °C

### Optional Features

GSM TECHNOLOGY

HOOTER SYSTEM

EXTRA TRAY

### Features

Eco Friendly PUF Insulation has thickness of 80mm.

Projected door prevents condensation & allows product view. Inner & outer doors are sealed around the entire perimeter by silicone sponge rubber gasket.

Bullet feet with in-built screwing adjustment are specially designed for long life under heavy load.

Heavy Duty refrigeration system, maintenance free, with hermetically sealed refrigeration compressors and reliable refrigeration to minimize noise and vibration.

#### 21 CFR PART-11 Compliance

Log data, Event data, Audit Trail data, E-Records & E-signatures, Graphical analysis & Data acquisition.

### Sizes:

Models	MK*-27DF	MK*-57DF
Features	275 Ltrs	575 Ltrs

#### Interior Dimension

Width in mm	700	800
Depth in mm	400	600
Height in mm	1000	1200

#### Exterior Dimension

Width in mm	930	995
Depth in mm	990	1190
Height in mm	1770	1955

#### Trays

No of Trays	2	3
Type	Wiremesh Type	
Tray Spacing	Every 1/2" Adjustable	

#### Power Supply

Power Supply	Single Phase, 230V 50Hz	
Power Rating	1.5KW	2KW
Warranty	12 Months	

Other sizes also available as on requirement.

Models	Material of Construction	
	Interior	Exterior
MK1	S.S.304 Dull Finish	G.I. Powder Coated
MK2	S.S.304 Dull Finish	S.S.304 Dull Finish
MK3	S.S.316 Dull Finish	S.S.304 Dull Finish

#### NOTE:

MK\* :- MK1 / MK2 / MK3

Accuracy & uniformity  $\pm 3$  °C applicable only with load